Filtersorb SP3 Sizing Information

The following tank sizes, liter usage, etc. relates to water with under 25 grains of hardness. It is recommended that you increase the Filtersorb SP3 liter usage by 5% per each additional 5 grains of hardness above 25 grains. The following systems are recommended up to 100 gallons per minute, for larger systems or questions about usage please contact Watch Water USA directly at 800-787-5300.

Residential Systems

Tank Size	Pipe Size	Flow Rate	Media Liters	Gravel Lbs.	Ship Weight
8 x 35	1"	10 gpm	3.5	N/A	30
9 x 35	1"	12 gpm	4	N/A	32
10 x 54	1"	15 gpm	4.5	N/A	37
12 x 52	1"	20 gpm	6.5	N/A	45
13 x 54	1"	25 gpm	7.5	N/A	51

Commercial Systems

Tank Size	Pipe Size	Flow Rate	Media Liters	Gravel Lbs.	Ship Weight
9 x 35	1"	12 gpm	5.5	N/A	32
10 x 54	1"	15 gpm	6.25	N/A	37
12 x 52	1"	20 gpm	9.25	N/A	45
13 x 54	1"	25 gpm	11	N/A	51
14 x 65	1"	30 gpm	12.5	N/A	77
16 x 65	1.5"	50 gpm	16.5	50	138
21 x 62	1.5"	70 gpm	28	100	250
24 x 72	2"	100 gpm	40	200	500